

FTL Series

ACs designed
exclusively for you.



PM 2.5 FILTER



POWER
CHILL



DRY MODE
FUNCTION



SELF DIAGNOSIS



GOOD SLEEP
OFF TIMER



CHILD LOCK

KEY FEATURES



5 YEARS WARRANTY
ON COMPRESSOR



1 YEAR COMPREHENSIVE
WARRANTY ON MACHINE



*STABILIZER FREE
OPERATION



ECONO MODE



COANDA
AIRFLOW



POWER-AIRFLOW
DUAL FLAPS



DNNS SELF
HEAL COATING



SMELL PROOF
OPERATION

SPECIFICATIONS

Model name		Indoor unit (IDU)	FTL30UV16V1
		Outdoor unit (ODU)	RL30UV16V1
Star Rating*			3 Star
Rated Power supply (Phase /Frequency/Voltage)			1φ/50Hz/230V (220-240V)
Power Supply Intake			Outdoor unit
Rated Cooling Capacity		kW	2.93
		Btu/h	10000
Rated Power Consumption	Cooling	W	742
Rated Annual Power Consumption		kWh	574.39
Rated ISEER		Wh/Wh	3.95
Operating Current	Cooling	A	3.4
Indoor unit (IDU)	Panel Color		White
	IDU Dimension (HxWxD)		298 x 885 x 229
	Package Dimension (HxWxD)		375 x 980 x 325
	IDU Net Weight (Gross Weight)		11 (14)
	Airflow Rate	Cooling	Feet ³ /min(cfm)
m ³ /min(cmm)			16.4
Operation sound H/M/ML/L/SL	Cooling	dBA	46/40/34
Outdoor unit (ODU)	ODU Dimension (HxWxD)		550 x 675 x 284
	Package Dimension (HxWxD)		620x 825 x 400
	ODU Net Weight (Gross Weight)		26.5 (32.5)
	Compressor Type		Rotary Compressor
	Refrigerant		R-32
Breaker size		A	15
Piping length	Charge-Less		10
	Max. Length	m	20
	Max. Height		15
Piping Connection	Gas/Liquid	mm(inch)	Φ9.5 / Φ6.4(3/8"/1/4")
Operating Ambient Temperature Range		Cooling(Min-Max)	°CDB 19.4-50

Measurement conditions:

1. Cooling capacity is based on: indoor temp. 27° CDB, 19° CWB; outdoor temp. 35° CDB, piping length 5 m.

2. Sound levels are based on temperature conditions 1. above with 5m piping length. These are anechoic conversion values. These values are normally somewhat higher during actual operation as result of ambient conditions.

Cooling and heating capacities above are rounded off to first decimal. 1TR (Ton of Refrigeration) = ~3.517 kilowatt.

**Star Rating mentioned as per ISEER Table 3.2 f, defined by Bureau of Energy Efficiency (BEE), Ministry Of Power.

* Value given in Inch. *As per Continuing Policy of Product Innovation at Daikin, The Design, Technical Specifications, Features, Look may change without prior Notice.

*Stabilizer Free Operation range 160-264 volt.

DAIKIN AIRCONDITIONING INDIA PVT. LTD.

12th Floor, Building No. 9, Tower A, DLF Cyber City, DLF Phase III, Gurgaon 122002, Haryana, India. Tel: 0124-4555444, Fax: 0124-4555333.

Customer Contact Centre:

SMS: <DAIKIN> to 92 101 88 999

Give missed call to: 92 101 88 999

Customer Support no.: 011-40319300 / 1860 180 3900

Email: customerservice@daikinindia.com

Visit us at: www.daikinindia.com

Follow us on:

www.facebook.com/daikinindia

www.twitter.com/daikinindia

www.instagram.com/daikinindia

in.company/daikin-airconditioning-india-pvt.-ltd.

www.youtube.com/user/DaikinACIndia

Disclaimer

As a continuing policy of product innovation at Daikin, the design and specifications are subject to change without prior notice. The visuals of the products in the leaflet are representative only, actual products might differ from the ones shown.

Products mentioned in this leaflet comply with RoHS regulations as per E-waste (Management & Handling) Rules, 2011 and should not be mixed with general household waste at the end of their useful life. For more details kindly visit our website www.daikinindia.com or contact our customer care centre at 011-40319300 / 1860 180 3900.